ELECTROMAGNETIC LIFTER

These magnets are compact, mobile, self-contained using a heavy duty 12 volt battery. Operating on this battery source they are free of restrictive cords and wires. They also have the added advantage of being useful in areas where electricity is not available.

Features

- The battery charger has an automatic cut-off prevent over-charging battery
- Audible Warning Alarm & Flashing Light indicates low battery
- Interlock prevents magnet de-energization when suspended in air
- Remote control keeps the operator a safe distance while operating the magnet.
- Safety switch prevents de-mag unless the load is safely on the ground






Applications

Steel service centers, Mold and die shop, Fabricators, Heat treating, steel mills, Steel warehouse





Battery Powered magnets use a heavy-duty 12VDC battery and can be turned on and off using a touch pad mounted on the front of the magnet or a hand held I/R remote transmitter.

Dimensions mm(inch)

Model	Size	Safe Working Load	Length	Width	Height to crane hook	Net weight	Ship weight
НВР	1300	1350 kg/3000 lb	414 (16.3)	218 (8.6)	559 (22)	86 kg / 190 lbs	91 kg / 200 lbs
HBP	2500	2500 kg/5500 lb	533 (21)	244 (9.6)	584 (23)	125 kg / 275 lbs	132 kg / 290 lbs
HBP	3600	3640 kg/8000 lb	1219 (48)	244 (9.6)	584 (23)	254 kg / 560 lbs	263 kg / 580 lbs
HBP	5000	5000 kg/11000 lb	1524 (60)	305 (12)	584 (23)	295 kg / 650 lbs	318 kg / 700 lbs

Batteries not included